

WHITE
220108

FLEX ONE PRO 171
HYBRID POLYURETHANE SEALANT
COLOR : WHITE

EXP.06/2023 LOT NO. 220108

USE:

- *Bonding applications in construction and metal constructions.
- *Strong elastic bonding in vibrating constructions.
- *Sealing of floor joints and joint precast wall.
- *Sealing of windows and door can be paintable

600 ml 15.55g /Box





Flex One
フレックス ワン

Constuction Sealant

FLEXONE

PRO 171 HYBRID SEALANT

FLEXONE PRO171 HYBRID SEALANT is a high modulus general purpose sealant for caulking and sealing uses. It is paintable and non- shrinking after curing, with good durability and anti-mold performance.

APPLICATION

- Facades Joint concrete.
- Around window and door frame.
- Over painting
- Sealant for waterproofing

ADVANTAGES

- No Isocyanate or silicone oil contaminates
- Paintable and non-shrinking after curing
- Resistant to water and mildew
- Permanent strength and elasticity
- Japan F**** environmental standard.

PRODUCT POPERTIES

Characteristics	HYBRID SEALANT
Curing type	Moisture curing type
Tack free time (min)	30 ~ 48 hours
Full curing time (day)	7 to 14 days
Specific gravity	1.70±0.1
Hardness (shore A)	40~50
Tensile strength (MPa)	10~15
Tolerance of movement (%)	±25
Elongation (%)	350
Application temperature range	5°C~40°C

ASTM C 920 [Type S, Grade NS, Class 25]

PACKAGE

- 600 ml. Sausage pack
- 20 Sausage / Box


STORAGE

- Recommend to store at dry place and 5°C~25°C

COLORS



WHITE



Concrete Grey

